

# 3-Way NPT Female Globe Valves (AT&AM)

Specification and Installation Instructions

### **Series**

GM AxxxxYB1: ½", 3-way, NPT female GM BxxxxYB1: ¾", 3-way, NPT female GM CxxxxYB1: 1", 3-way, NPT female GM DxxxxYB1: 1-¼", 3-way, NPT female GM ExxxxYB1: 1-½", 3-way, NPT female GM FxxxxYB1: 2", 3-way, NPT female



#### **Features**

- Linear actuator with digital or analog input for 3-way water or low-pressure steam applications.
- Delivers up to 100 lbs (450 N) with reversible stroke direction.
- Optional DDSTM kit protects actuator from steam heat (The kit is available separately and factory installed).

## **Models**

Size	3-Way Models	Cv	Kv	Close Off PSI
1/"	GM A0022YB1	2.2	1.9	250
	GM A0044YB1	4.4	3.8	250
3/,"	GS B0075YB1	7.5	6.4	180
1"	GM C0140YB1	14	12	100
1-1/4"	GM D0200YB1	20	17	65
1-1/2"	GM E0280YB1	28	24	45
2"	GM F0410YB1	41	35	25


#### **Technical Data**

Specification		All Models		
-				
Actuator Compatibility		All Neptronic AT & AM series actuators		
Sizes		½" to 2"		
Range Cv [Kv]		0.4 to 41 [0.3 to 35]		
Fluid Temperature		Water: +40°F to +281°F (+4°C to +138°C)		
		Steam: +230°F (+110°C) Maximum (For steam applications, add <u>BBDDSTM</u> .)		
Valve Flow Type		3 Way: Linear		
Static Pressure		Water: 250 PSIG Maximum		
Inlet Pressure		Steam: 15 PSIG Maximum		
Maximum Differential Pressure		Water: 10 PSIG Recommended, (35 PSIG Maximum)		
		Steam: 15 PSIG Maximum		
	Body & Seat	Bronze ANSI B16.15 Class 250		
Materials	Stem	Stainless Steel		
	Plug	Brass		
	Packing	Spring Loaded Teflon Cone		
End Connections		Standard NPT Female		




### **Dimensions**

### 3 Way, 1/2" - 2" NPT with AT Actuators



Valve Size	Valve Model Prefix	Α	В	С
1/,"	GM A0022YB1	3.00	7.16	1.38
1/2"	GM A0044YB1	3.00	7.16	1.38
3/4"	GS B0075YB1	3.63	7.16	1.69
1"	GM C0140YB1	4.63	7.22	1.56
1-1/4"	GM D0200YB1	4.63	7.47	1.63
1-1/2"	GM E0280YB1	5.38	7.59	1.63
2"	GM F0410YB1	6.13	7.66	1.88

3 Way, 1/2" - 2" NPT with AM Actuators



Valve Size	Valve Model Prefix	Α	В	С
1/2"	GM A0022YB1	3.00	8.16	1.38
1/2"	GM A0044YB1	3.00	8.16	1.38
3/4"	GS B0075YB1	3.63	8.16	1.69
1"	GM C0140YB1	4.63	8.22	1.56
1-1/4"	GM D0200YB1	4.63	8.47	1.63
1-1/2"	GM E0280YB1	5.38	8.59	1.63
2"	GM F0410YB1	6.13	8.66	1.88

**Note:** All dimensions are measured in inches and may vary depending on the supplier. Changes can occur without prior notice.



Recycling at end of life: please return this product to your Neptronic local distributor for recycling. If you need to find the nearest Neptronic authorized distributor, please consult www.neptronic.com.